

BRAKE FLUID



PENTOSIN SUPER DOT 4

Corrosion Resistant Universal Brake Fluid

DESCRIPTION

Pentosin Super DOT 4 is a brake fluid of superior quality for universal use in modern brake systems and ideal for vehicles with ABS systems. Pentosin Super DOT 4 offers safety against vapor lock; it has excellent resistance to absorbing and retaining water and provides superior corrosion resistance.

PRODUCT ATTRIBUTES

Appearance	Yellow & Clear
Density at 20°C	1065 kg/m ³
Kinematic Viscosity at 40°C	7.9 mm ² /s
Kinematic Viscosity at 20°C	14.5 mm ² /s
Kinematic Viscosity at -40°C	≤ 1500 mm ² /s
Melting Point	>-50°C/>-58°F
Flash Point	130°C/266°F
Ignition Temperature	>200°C/>392°F
Boiling Point	≥265°C/≥509°F
Wet Boiling Point	≥165°C/≥329°F
pH Value	8

SIZE	PART NUMBER	GTIN-13
0.25 Liter	1204112	4008849204036
0.5 Liter	1204114	4008849204067
1 Liter	1204116	4008849204074
5 Liter	1204204	4008849204159

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	B 000 700 A1
Audi/Volkswagen	B 000 700 A3
Audi/Volkswagen	B 000 700 A6
BMW/MINI	81 22 9 407 510
BMW/MINI	81 22 9 407 511
BMW/MINI	81 22 9 407 512
BMW/MINI	81 22 9 407 513
Land Rover	LRNDOT4
Mercedes-Benz	000 989 08 07 10
Mercedes-Benz	000 989 08 07 11

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Mercedes-Benz	000 989 08 07 19
Porsche	000 043 203 66
Porsche	000 043 203 67
Porsche	000 043 305 52

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
MAN	TUC 6518/07
FMVSS	No. 116 DOT 4
ISO	4925 Class 4
SAE	J1704

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of Deutsche Pentosin-Werke. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOSUPERDOT4-112917



OE-quality brands for import applications.