

TRANSMISSION
FLUID



PENTOSIN ATF1 LV

Long-Life Fully Synthetic Automatic Transmission Fluid

DESCRIPTION

Pentosin ATF 1 LV is a fully synthetic high performance Automatic Transmission Fluid (ATF) for life-time application in automatic gear boxes. It can be used when a “low viscosity” ATF is required. Pentosin ATF 1 LV is formulated by means of the best commercially available synthetic base oils and additive components. A high performance shear stable VI-Improver plus modern antiwear chemistry and friction modifiers guarantee a sound stable friction performance in modern automatic transmissions equipped with an electronically controlled converter clutch.

PRODUCT ATTRIBUTES

Appearance	Red & Clear
Density at 20°C	845 kg/m ³
Kinematic Viscosity at 100°C	5.6 mm ² /s
Kinematic Viscosity at 40°C	25.3 mm ² /s
Viscosity Index	168
Dynamic Viscosity at -40°C	6,800 mPa*s
Pour Point	-54°C/-65.2°F
Flash Point	>206°C/>402°F

SIZE	PART NUMBER	GTIN-13
1 Liter	1088107	4008849173448
5 Liter	1088206	4008849173462

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© 2016 CRP Industries Inc. Pentosin is a trade name of Deutsche Pentosin-Werke. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOATF1LV-060116



OE-quality brands for import applications.