

**TRANSMISSION
FLUID**



PENTOSIN FFL-2

Fully Synthetic Double Clutch (DSG) Transmission Fluid

DESCRIPTION

Pentosin FFL-2 is the only approved first fill and service fill transmission fluid for the new generation of AVW double clutch gear transmissions (DSG). Pentosin FFL-2 is founded on a fully synthetic base oil technology for safe operation at even the highest thermal load. FFL-2 features a special clutch friction performance which makes it mandatory to be applied solely to the double clutch gear box – do not mix with any other gear oils.

| SIZE | PART NUMBER | GTIN-13 |
|----------|-------------|---------------|
| 1 Liter | 1038107 | 4008849174216 |
| 20 Liter | 1038208 | 4008849172212 |

PRODUCT ATTRIBUTES

| | |
|-----------------------------|-------------------------|
| Appearance | Amber & Clear |
| Density at 15°C | 845 kg/m ³ |
| Density at 20°C | 841 kg/m ³ |
| Kinematic Viscosity at 40°C | 36.3 mm ² /s |
| Viscosity Index | 173 |
| Dynamic Viscosity at -40°C | 12100 mPa*s |
| Pour Point | -51°C/-59.8°F |
| Flash Point | 224°C/435.2°F |
| pH Value | N/A |

OE REFERENCE NUMBERS/RECOMMENDATIONS

| Make | Reference Number |
|-----------------|------------------|
| Audi/Volkswagen | G 052 182 A2 |
| Audi/Volkswagen | G 052 182 A6 |

APPROVALS/SPECIFICATIONS

| Organization Name | Specification Met |
|-------------------|-------------------|
| Audi/Volkswagen | TL 521 82 |

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© 2016 CRP Industries Inc. Pentosin is a trade name of Deutsche Pentosin-Werke. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOFFL2-060116



OE-quality brands for import applications.