



# PENTOSIN MTF 2

## Fully Synthetic All-Purpose Manual Transmission Fluid

### DESCRIPTION

**Pentosin MTF 2** is a fully synthetic gear oil with all purpose performance for manual transmissions. This manual transmission oil is formulated with modern EP-additives, high shear stable VI improvers and premium synthetic base oils. Pentosin MTF 2 improves synchronization characteristics and was lowered to SAE 75W-80 for better fuel economy.

### PRODUCT ATTRIBUTES

Appearance	Amber & Clear
Density at 15°C	851 kg/m <sup>3</sup>
Density at 20°C	850 kg/m <sup>3</sup>
Kinematic Viscosity at 100°C	7.7 mm <sup>2</sup> /s
Kinematic Viscosity at 40°C	38.3 mm <sup>2</sup> /s
Kinematic Viscosity at 20°C	88 mm <sup>2</sup> /s
Viscosity Index	177
Dynamic Viscosity at -40°C	7600 mPa*s
Pour Point	<-60°C/<-76°F
Flash Point	228°C/442.4°F
Ignition Temperature	330°C/626°F
pH Value	N/A

SIZE	PART NUMBER	GTIN-13
1 Liter	8056107	4008849112331
5 Liter	8056206	4008849135545

### OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
BMW	83 22 0 309 031
BMW	83 19 2 344 627
Hyundai	00232-19041
Hyundai	00232-19042

### APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
API	GL-4

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© 2016 CRP Industries Inc. Pentosin is a trade name of Deutsche Pentosin-Werke. All rights reserved.

**DISCLAIMER:** CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOMTF2-060116